PUBLIC ADDRESS / SPEAKERS / CEILING

SKY-5T-DOME

5' + 1' CEILING LOUDSPEAKER WITH 100 V LINE TRANSFORMER AND LOW IMPEDANCE

- 5' + 1' coaxial speaker. 15/10/5/2.5 W RMS@100 V and 15 W RMS@8 ?
- Protective dome type back cover
- Low profile aluminium grille
- Fast connection terminals and high conductivity. In junction box
- Anti-fall system for installation assistance

+ Info:
https://fonestar.com/SKY-5T-DOME

ESPECIALLY RECOMMENDED IN:

Hospitality

Retail

Hotels

All sectors

DESCRIPTION

5' coaxial ceiling speaker with 1' tweeter and rear dome cover. 15/10/5/5 W RMS@100 V and 15 W RMS@8 Ohm. Low profile grille.

TECHNICAL CHARACTERISTICS

FEATURES	Ceiling loudspeaker with 100 V line transformer and low impedance. Protective dome type back cover. Low profile frameless grille, constructed from rust resistant aluminium. Detachable, turn-lockable grille. The logo can be removed and painted. Fast connection terminals and high conductivity. Junction box in the rear cover with inlet and outlet port. Anti-fall system for installation assistance. Hook for safety cable. Stable, worm-gear ceiling brackets. Installation in ceilings with limited space. Protection against dust and water.
POWER	15 W RMS 20 W MAX.
SPEAKER	Coaxial loudspeaker. 5" polypropylene woofer 1" swivelling tweeter
RESPONSE	100-20.000 Hz @ -10 dB 120-20.000 Hz @ -3 dB
IMPEDANCE	15 W RMS@100 V (666 Ohm) 10 W RMS@100 V/70 V (1.000 Ohm/490 Ohm) 5 W RMS@100 V/70 V (2.000 Ohm/980 Ohm) 2'5 W RMS@100 V / 70 V(4.000 Ohm/ 1.960 Ohm) 1.25 W RMS@70 V (3.920 Ohm) Low Z: 8 Ohm
SENSITIVITY	86 dB @ 1 W/1 m
SOUND PRESSURE	98 dB @ max. W/1m Continuo 99 dB @ max. W/1m Pico

+ Info:
https://fonestar.com/SKY-5T-DOME

COVERAGE ANGLE	90º@1kHz (- 6 dB)
PROTECTIONS	IP-65 in compliance with IEC 60529 EN ISO 9227:2006 Neutral Salt Spray Test
MATERIAL	ABS (UV resistant) Liquid paint aluminium grille
CONNECTORS	Quick-connect terminals with high conductivity Conductor cross-section: 0.4–4 mm² Rubber cable glands for round cables with a diameter of 6–7 mm
SWITCH	W selector in high Z and 8 Ohm. Accessible from the front.
OPERATION TEMPERATURE	-20ºC ~ 70ºC (48 h)
STORAGE TEMPERATURE	10ºC ~ 40ºC
MAXIMUM HUMIDITY	95%
COLOUR	White (RAL 9003)
DIMENSIONS	Total loudspeaker: 214 mm Ø x 100 mm height Grille section: 5 mm Recessed height: 95 mm Installation hole: 180 mm Ø Maximum ceiling thickness: 30 mm
WEIGHT	1.3 kg
ACCESSORIES	Installation template

+ Info:
https://fonestar.com/SKY-5T-DOME

SPL vs Frequency



SPL vs Angle



Curve	Freq.	BW	Q	DI
	500.00	60	6.0	7.8
	1.00K	105	3.4	5.4
	2.00K	45	8.0	9.0
	4.00K	15	24.0	13.8

Impedance vs Frequency









Product: SKY-5-DOME + SKY-5T-DOME Line Drawings	FONESTAR www.fonestar.es
Date: 2025-06-12	