

PUBLIC ADDRESS / SPEAKERS / SURFACE

# SONORA-5-DANTE-BK

DANTE SURFACE SPEAKER



- ✓ Crisp, distortion-free sound
- ✓ Digital audio receiver via DANTE
- ✓ Class D amplifier
- ✓ Excellent finish and elegant design
- ✓ Quick and easy installation



+ Info:

<https://fonestar.com/SONORA-5-DANTE-BK>

## ESPECIALLY RECOMMENDED IN:



Hospitality



Education



Hotels



All sectors

## DESCRIPTION

5 ¼" DANTE surface speaker. 30 W RMS. Adjustable fixing mount. Steel safety cable.

## TECHNICAL CHARACTERISTICS

|                   |                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------|
| FEATURES          | Dante speaker.<br>Class D amplifier.<br>High sound quality, clear sound without distortion.                    |
| AMPLIFIER         | 60 W maximum, 30 W RMS                                                                                         |
| LOUDSPEAKERS      | 1 x 5 ¼" polypropylene woofer<br>1 x 1" tweeter                                                                |
| RESPONSE          | 80-20.000 Hz                                                                                                   |
| IMPEDANCE         | 8 Ohm                                                                                                          |
| SENSITIVITY       | 88.3 dB @ 1 W/1 m                                                                                              |
| PRESSURE          | 102.2 dB @ max. W/1 m                                                                                          |
| COVERAGE ANGLE    | H/V: 200°/200°@500Hz, 135°/135°@1kHz, 100°/120°@2kHz, 60°/80°@4kHz (-6 dB)                                     |
| MATERIAL          | ABS (UV resistance)<br>Aluminium mesh grille, with powder-coated finish<br>A2 stainless steel screws           |
| CONNECTORS        | 1 LAN port for connection to local area network and PoE+, RJ-45 plug                                           |
| TEMPERATURE RANGE | -10°C ~ 60°C                                                                                                   |
| COLOUR            | Black (RAL 9005)                                                                                               |
| POWER SUPPLY      | PoE+ (IEEE 802.3at) or 24 V DC, 2 A                                                                            |
| DIMENSIONS        | Loudspeaker: 162 x 263 x 147 mm depth<br>Mount wall plate: 68 x 110 mm<br>Loudspeaker with mount: 216 mm depth |
| WEIGHT            | 1.7 kg                                                                                                         |
| INCLUDES          | Adjustable mounting bracket ± 60° in all directions.<br>Steel safety cable                                     |



+ Info:

<https://fonestar.com/SONORA-5-DANTE-BK>

SENSITIVITY (SPL)

